



Made under



>> Type of uses (*)

Thanks to its technical features, this glove is particularly suitable for all heavy works which are not requiring a fine dexterity nor a protection against liquids: farmers, loggers, foresters, maintenance of green areas, building, logistics, dockworkers, etc.

>> Technical features

✓ Construction :

- « Canadian » style protective glove. Gunn Cut Pattern. One-piece forefinger. Cotton lined palm. Additional leather reinforcement around seams for extra service life. Ventilated canvas at rear. Rubberized safety cuff with vein protector in leather. Elastic tightener on back. Stitched with polyester yarn. Leather tipped fingers and knucklestrap.

Grain reinforcement on palm.

- ✓ Colour : Yellow leather; blue fabric.
- ✓ Material : split cow leather; cotton textile.
- ✓ Size : 10.
- ✓ Packing : - Carton of 50 pairs.
- Bundle of 10 pairs.



More information: www.singer.fr



>> Key strengths

- ✓ Very good resistance of the leather with a careful selection of hides.
- ✓ Quality of manufacture and assembly.
- ✓ Security flared cuff for quick removal in case of emergency.
- ✓ Wrist protection with a strong rubberized cuff.
- ✓ Traditional comfort of the leather particularly appreciated for its good breathability.
- ✓ Extra grain leather reinforcement on palm for added protection and longer service life.



>> Conformity

This glove has been tested according to the following European standards :

- EN 420 : 2003 + A1 : 2009. Protective gloves - General requirements and test methods.
- EN 388 : 2016. Protective gloves against mechanicals risks.



It complies with European Regulation (EU) 2016/425 on Personal Protective Equipment (PPE). Category II. EU type examination certificate (module B) issued by SGS. Notified body n°0120 / 0598.

Download the EU declaration of conformity on: <http://docs.singer.fr>

EN 388: 2016. Protective gloves against mechanical risks							
Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels	 3 1 2 2 X
Abrasion resistance (number of cycles)	100	500	2000	8000	-	3	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	1	
Tear resistance (in Newtons)	10	25	50	75	-	2	
Perforation resistance (in Newtons)	20	60	100	150	-	2	
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level
	2	5	10	15	22	30	X

«X» means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**

