




>> Use (*)

Thanks to its conception, this glove can be used as an electrical over-glove to assure a better protection and a longer longevity. This glove is suitable for heavy handling in dry conditions.

Can't be used alone against electrical risk.

>> Technical features

- ✓ **Construction** : Cut and sewn liner. «American» construction. Straight thumb. Knitted cuff. Adjustment with hook-and-loops-flap on the back.
- ✓ **Material** : Cow grain leather palm and back. Split leather cuff, 10 cm.
- ✓ **Colour** : beige glove, grey cuff.
- ✓ **Sizes** : 9, 10, 11.
- ✓ **Packing**: Carton of 50 pairs. Bundle of 5 pairs. 

Learn more : www.singer.fr



>> Advantages

- ✓ Good quality leather, flexible and resistant.
- ✓ Palm and wide cuff to position the equipment over an electrician's glove.
- ✓ Protects the electrician's glove against external aggressions and increases its life.
- ✓ Practical fit in the back of the cuff.

>> Conformity


This glove has been tested according to the following European standards :

- **EN 420 : 2003 + A1 : 2009**. Protective gloves - General requirements and test methods.
- **EN 388 : 2016**. Protective gloves against mechanicals risks.



It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II**. EU type examination certificate (module B) issued by **SGS**. Notified body **n°0120**.

EN 388: 2016. Protective gloves against mechanical risks

| Mechanical data. Information about levels. | Level 1 | Level 2 | Level 3 | Niveau 4 | Level 5 | Levels ▼ | EN 388 : 2016  3 1 2 1 X |
|---|---------|---------|---------|----------|---------|----------|---|
| Abrasion resistance (number of cycles) | 100 | 500 | 2000 | 8000 | - | 3 | |
| Blade cut resistance (index) | 1,2 | 2,5 | 5,0 | 10,0 | 20,0 | 1 | |
| Tear resistance (in Newtons) | 10 | 25 | 50 | 75 | - | 2 | |
| Perforation resistance (in Newtons) | 20 | 60 | 100 | 150 | - | 1 | |
| Cut resistance (N) (as per EN ISO13997) (TDM test) | Level A | Level B | Level C | Level D | Level E | Level F | Level |
| | 2 | 5 | 10 | 15 | 22 | 30 | X |

«X» means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**

