

>>Type of use (*)









Light industry

Heavy industry

Structural Maintenance works

Public works

>> Technical features

- ✓ Temporary anchoring.
- Polyester strap ring.
- ✓ Width: 25 mm.
- ✓ Length: 60 cm.
- ✓ Weight: 90 g.

→ Packing:

- carton of 20 pieces.
- bundle of 1 piece.



Learn more: www.singer.fr

>> Advantages

- → To guarantee the best quality, the production line is fully integrated.
- ✓ We control and produce in a single factory the design and fabrication of the products: weaving coated thread into straps, stamping metal pieces and chemical treating, harness assembly, individual control and real-time testing thanks to the different laboratory devices and tools etc...
- ✓ ISO 9001 manufacturing which guarantees product reliability and rigorous monitoring of the production process.

>> Conformity

This product has been tested according to the following European standard:

- EN 795: 2012. Personal protective equipment against falls from a height. Anchor devices.

EN 795: 2012 Class B C € 0598

It complies with European Regulation (EU) 2016/425 on Personal Protective Equipment (PPE).

Category III.

EU type examination certificate (module B) issued by SATRA (Ireland). Notified body n°2777.

The PPE is subject to the conformity assessment procedure based on quality assurance of the production process (**Module D**) set out in Annex VIII (Category III) under surveillance of **SGS Fimko Oy (Finland)**. Notified body **n°0598**.

Download the EU declaration of conformity on: http://docs.singer.fr



