



990 g

2.00 m



>> Type of use (\*)



Light industry    Heavy industry    Structural works    Maintenance    Public works

>> Technical features

- ✓ Retractable fall arrester with polyester strap.
- ✓ Having a protective casing.
- ✓ Includes a light double action aluminium connector, captive with swivel.
- ✓ Includes a triple action aluminium connector OVALUX.
- ✓ Total length: **2.00 m**.
- ✓ Weight: **990 g**.
- ✓ Packing:
  - carton of 1 piece.



Learn more: [www.singer.fr](http://www.singer.fr)

>> Advantages

- ✓ Presence of a fall witness.
- ✓ Visible energy absorber.
- ✓ **Possible use in factor 2.**
- ✓ Very light weight (990 g) and easy to carry.
- ✓ **ISO 9001** certified manufacturing.



EN 360: 2002

CE 0598

>> Conformity

This product has been tested according to the following European standard:

- **EN 360: 2002.** Personal Protective Equipment against falls from a height. Retractable lanyards.
- **CNB/P/11.060: 2014.** Co-ordination of notified bodies. Vertical Recommendation for Use sheets (RfUs). VG11.

It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category III.** EU type examination certificate (**module B**) issued by **SATRA (Ireland)**. Notified body n°2777.

The PPE is subject to the conformity assessment procedure based on quality assurance of the production process (**Module D**) set out in Annex VIII (Category III) under surveillance of **SGS Fimko Oy (Finland)**.

Notified body n°0598.

Download the EU declaration of conformity on: <http://docs.singer.fr>

Your distributor **SINGER® SAFETY**

**SINGER®**   
safety