

>>Type of use (*)











Light industry

industry

Structural Maintenance

>> Technical features

- → Braided polyester rope.
- → Compatible with the mobile fall arrester on rope STOPRO.
- ✓ Not compatible with the mobile fall arrest system STOPLUX.
- → Diameter: 12 mm.
- ✓ Length: 20 meters.
- ✓ Weigth: 2.40 kg.
- ✓ Packing:
 - carton of 10 units.
 - boxes of 1 unit.



Learn more: www.singer.fr

>> Advantages

- ✓ One termination with splices protected with a plastic sheath and loop with plastic reinforcement thimble. This prevents the rope from being damaged by the metallic contact of a connector.
- → Also available in 10 meters length (ref: ASSULINE100).
- ✓ ISO 9001 certified manufacturing.

EN 353-2: 2002 **C** € 0598

>> Conformity

This product has been tested according to the following European standard:

- EN 353-2: 2002. Personal Protective Equipment Against Falls From A Height.-

Part 2: Guided Type Fall Arresters Including A Flexible Anchor Line

It complies with European Regulation (EU) 2016/425 on Personal Protective Equipment (PPE). Category III. EU type examination certificate (module B) issued by SATRA (Ireland). Notified body n°2777.

The PPE is subject to the conformity assessment procedure based on quality assurance of the production process (Module D) set out in Annex VIII (Category III) under surveillance of SGS Fimko Oy (Finland). Notified body n°0598.

Download the EU declaration of conformity on: http://docs.singer.fr

Your distributor SINGER® SAFETY

