



>> Use (*)

Especially suitable for works in logistics, tertiary sector. For all types of jobs requiring high mobility and comfort. Tiler, driver, warehousing, storage, printing, transport... (Avoid use in highly aggressive or dirty environments).

>> Technical features

- ✓ Low cut safety shoes, metal free
- ✓ Split suede leather and ventilated polyester mesh.
- ✓ 200J shockproof composite toe cap.
- ✓ Comfortable padding tongue.
- ✓ Antistatic and removable insole made of EVA fabric.
- ✓ High strength textile puncture resistant midsole.
- ✓ Double-density polyurethane sole.
- ✓ Grey colour, orange stitching.
- ✓ Sizes : 36 to 47.
- ✓ Packing : Carton of 10 pairs. Bundle of 1 pair.



490g⁽¹⁾

⁽¹⁾ Approximative weight of a shoe (smaller size)

Learn more : www.singer.fr

>> Advantages

- ✓ Lightweight, flexible and very aesthetic model. Suitable for men and women.
- ✓ The shape of the insole provides excellent shock absorption and comfort.
- ✓ The holes let the sweat go through and keep the foot always dry.
- ✓ The composition and the structure of the Mesh lining allow the foot to breathe.
- ✓ Dual density sole, antistatic, slip resistant, resistant to oils and hydrocarbons, produced by injection directly on the upper, ensures a high resistance to mechanical stress.
- ✓ Shoes sold with an extra pair of grey laces.
- ✓ The **ISO 9001 / ISO 14001** certified production guarantees the reliability / regularity of the production and the control of the environmental impact.



>> Compliance



This safety shoe has been tested according to the following European Standard (Category II).

- **EN ISO 20345: 2012.** Personal protective equipment - Safety footwear.

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE).

EU type examination certificate (module B) issued by **CIMAC (Italy)**, notified body n°0465.



Protection	Symbol S1P	General requirement of the standard EN ISO20345. Toe protection against shocks equivalent to a level of energy equal to 200J and the risks of flattening under a maximal weight of 15 kN. + closed back + anti-static properties + heel energy absorption + Resistance to fuel oil + Puncture resistant midsole
Slip resistance	Symbol SRC	(= SRA + SRB) Slip resistance on ceramic tile floor with SLS and on steel floor with glycerol

Your distributor **SINGER® SAFETY**

