



1.50 m \varnothing 12 mm



>> Type of use (*)



Light industry



Heavy industry



Structural works



Maintenance



Public works

>> Technical features

- ✓ Lanyard in polyamide.
- ✓ Length 1.50 m.
- ✓ Made up of 12 mm diameter, 3 strand polyamide rope.
- ✓ The splices are protected with a sleeve.
- ✓ Two sides thimble loops.
- ✓ Packing:
 - Carton of 50 pieces.
 - Bundle of 1 piece.



Learn more: www.singer.fr

>> Advantages

- ✓ The spliced end is protected with a strong transparent protective covering sleeve.
- ✓ This not only protects the splicing but also make the splicing visible for easy inspection prior to use.
- ✓ The loops at the end are protected by an abrasion resistant thimble. This prevents the rope from being damaged by the metallic contact of the connector.
- ✓ The rope also has a coloured tracer strand which loses its colour in due course of time, to show that the lanyard is now unfit for further use.
- ✓ ISO 9001 certified manufacturing.



>> Conformity

This product has been tested according to the following European standard:
EN 354: 2002. Personal protective equipment against falls from a height. Lanyards



It complies with **European Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category III.**
 EU type examination certificate (**module B**) issued by **SATRA (Ireland)**. Notified body n°2777.
 The PPE is subject to the conformity assessment procedure based on quality assurance of the production process (**Module D**) set out in Annex VIII (Category III) under surveillance of **SGS Fimko Oy (Finland)**. Notified body n°0598.

Download the EU declaration of conformity on: <http://docs.singer.fr>

Your distributor **SINGER® SAFETY**



(*) Type of use is given as a guide only. It is to the end user to check whether the product is suitable or not for the intended use. Before any use, read carefully the instructions enclosed with the product. Issue LS_2019_12_27. Copyright: Singer, Fodlia.