



815 g

1.00 m Ø 12 mm



>> Type of use (*)



Light industry



Heavy industry



Structural works




Maintenance



Public works

>> Technical features

- ✓ Restraint lanyard.
- ✓ Stranded polyamide rope. Splices on both sides.
- ✓ Includes a double action steel connectors GRABPRO.
- ✓ Includes a steel screw connector OVABASE.
- ✓ Weight: **815 g.**
- ✓ Length: **1.00 meter.**
- ✓ Diameter: **12 mm.**
- ✓ **Packing:** - carton of 10 pieces.
- under individual polybag. 

Learn more: www.singer.fr

>> Advantages

- ✓ Each end of the lanyard with a connector included.
- ✓ The loops at the ends of the lanyards are protected by an abrasion resistant thimble. This prevents the rope from being damaged by the metallic contact of the connector.
- ✓ **ISO 9001** certified manufacturing.



>> Conformity

This product has been tested according to the following European standard:
EN 354: 2002. Personal protective equipment against falls from a height. Lanyards



It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category III.**
EU type examination certificate (**module B**) issued by **SATRA (Ireland)**. Notified body n°2777.
The PPE is subject to the conformity assessment procedure based on quality assurance of the production process (**Module D**) set out in Annex VIII (Category III) under surveillance of **SGS Fimko Oy (Finland)**. Notified body n°0598.

Download the EU declaration of conformity on: <http://docs.singer.fr>

Your distributor **SINGER® SAFETY**

