



### >> Use (\*)

Thanks to its technical characteristics, this glove is suitable for all major works requiring dexterity and a good protection against mechanical risks including cut, as per EN388 European standard). Industrial maintenance, automotive assembly, general handling, making cables, cardboard factory, metal sheet manufacture, aircraft assembly, engineering works...

### >> Technical features

- ✓ Seamless knitter liner. HDPE fibers (High Density Polyethylene). Open back (ventilated). Elasticated knitted wrist.
- ✓ **Color:** grey.
- ✓ **Gauge:** 13.
- ✓ **Coating:** Soft polyurethane (PU) coating on palm.
- ✓ **Sizes:** 6 to 11.
- ✓ **Packing:** - carton of 100 pairs.  
- bundle of 10 pairs.



Learn more : [www.singer.fr](http://www.singer.fr)

### >> Advantages

- ✓ **Seamless knitting:** the seamless liner provides exceptional comfort and reduces hand fatigue. There is no roughness. There are no rubbing points (no seams!). The knitting has natural elasticity allowing the glove to fit perfectly around the hand.
- ✓ **High technicity fibres:** HDPE fibres provide excellent protection against mechanical risks, namely cut protection
- ✓ **Protective coating:** the polyurethane (PU) coating on palm provides additional protection to the user as well as slip resistance for a better grip.



### >> Conformity

This glove has been tested according to the following European standards :

- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanicals risks.

It complies with **European Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). Category II.

EU type examination certificate (**module B**) issued by **SATRA**. Notified body n°2777.



EN 388: 2016. Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Level 4	Level 5	Level ▼	
	Abrasion resistance (number of cycles)	100	500	2000	8000	-	4
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	3	
Tear resistance (in Newtons)	10	25	50	75	-	4	
Perforation resistance (in Newtons)	20	60	100	150	-	3	
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level ▼
	2	5	10	15	22	30	B

**EN 388 : 2016**

4 3 4 3 B

«X» means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**



(\*) Type of use is given as a guide only. It is to the end user to check whether the product is suitable or not for the intended use. Before any use, read carefully the instructions enclosed with the product. Issue CL 05/02/2019. Copyright: Singer