


81 g



[ Standard ]



>>Use (\*)

Thanks to its technical characteristics, this equipment is particularly suitable for all major works requiring protection against mechanical risks and projections including: grinding, sanding, cutting, polishing, carpentry, industry, do-it-yourself etc.

>> Technical features

- ✓ Safety google.
- ✓ Lightweight soft P.V.C frame.
- ✓ Integral lateral vents for wearer comfort.
- ✓ Adjustable headband.
- ✓ Lens in clear polycarbonate.
- ✓ Lens thickness: 1.50 mm.
- ✓ Dimensions: 152 mm x 79 mm.
- ✓ Weight: 81 g.
- ✓ Packing: - carton of 100 units.  
- box of 10 units.



Learn more [www.singer.fr](http://www.singer.fr)

>> Advantages

- ✓ Comfortable nose bridge.
- ✓ Adjustable elastic strap (400 mm).
- ✓ A standard model, soft and resistant for many applications.
- ✓ A good value for money.
- ✓ Security of an ISO 9001 system in production.



>> Conformity

This product has been tested according to the following European Standard:

✓ EN 166: 2001. Personal eye-protection. Specifications.

It complies with the European Regulation (EU) 2016/425 on Personal Protective Equipment (PPE). Category II.

EU type examination certificate (module B) issued by BSI (Netherlands). Notified body n°2797.

Download the EU declaration of conformity on: <http://docs.singer.fr>



Mechanical protection	Symbol <b>BT</b>	Medium energy impact resistant of particules thrown very fast (correspond with a 6 mm steel ball impact which would weight 0.86 g at the minimum and thrown at 120 m/s) at extremous temperatures.
Optical quality	Symbol <b>1</b>	Class 1: continuous works (better quality).
Designation	Symbol <b>4</b> <b>9</b>	4 : Large dust particles (Dust with particules of > 5 mm). 9 : Molten metal and hot solids: Molten steel projection and penetration of hot solids.

Your distributor SINGER® SAFETY

