


24 g




>>Uses (*)

Thanks to its technical characteristics, this equipment is particularly suitable for all major works requiring protection against mechanical risks and projections including: grinding, carpentry, polishing, industry, laboratories, sports etc ... UV protection.

>> Technical features

Safety spectacles. UV protecton. Anti-scratch and anti-fog treatment.

- ✓ **Lens** : single piece clear polycarbonate lens, thickness 2.00 mm.
- ✓ **Temples** : TPR + polycarbonate.
- ✓ **Nose bridge** : molded-in, polycarbonate.
- ✓ **Screw** : stainless steel.
- ✓ **Weight** : 24 g.
- ✓ **Packing** : - cartons of 100 pairs.
- customized box of 10 pairs. 
- each pair under individual polybag.

Learn more: www.singer.fr

>> Advantages

- ✓ EVAORAN protective spectacles provide high quality protection and a modern design.
- ✓ Dual-colored and bi-injected temples ensure a perfect fit of the equipment on the face.
- ✓ Molded-in nose bridge provides uncompromised comfort and fit.
- ✓ Perforated temples will allow the use of adjustable safety cord.
- ✓ The unique and rounded shape of the lens (9 °) allows both a field of view at 180 ° C and an optimum protection.
- ✓ Light weight, 24 g only!



>> Conformity

This product has been tested according to the following European Standards:

- ✓ **EN 166: 2001**. Personal eye-protection. Specifications.
- ✓ **EN 170: 2002**. Personal eye-protection. Ultraviolet filters. Transmittance requirements and recommended use.

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II**. EU type examination certificate (**module B**) issued by **BSI** (Netherlands). Notified body **n°2797**.

Download the EU declaration of conformity on: <http://docs.singer.fr>



Mechanical protection	Symbol FT	Impact resistant against high speed particles at high temperatures (corresponds to the impact of a steel ball with a diameter of 6 mm and a minimum mass of 0.86 g launched at 45 m/s).
Optical quality	Symbol 1	Class 1: continuous works (better quality).
Scale number	Symbol 2C.1.2	Colour perception: not impaired Typical application: for use with sources that emit UV radiation predominantly at wavelengths < 313 nm and when glare is not an important factor. This applies to UVC and most UVB radiation ^(b) . Typical source ^(a) : Low pressure mercury vapour lamps, such as those used to stimulate fluorescent or "black lights", actinic and germicidal lamps. <i>(a) The example given for typical source is for general guidance.</i> <i>(b) The wavelengths of these bands are recommended by IEC (that is UVB 280 nm to 315 nm & 100 nm to 280 nm for UVC).</i>

Your distributor **SINGER® SAFETY**

