

>> Use (*)

Use of this helmet is mainly recommended for any activity where there is a risk of impact on the upper part of the head by falling objects. The industry in general, construction, building, public works, quarries, etc.^(*)

>>Technical features

- ✓ Working safety ABS helmet.
- ✓ 8 points webbing suspension system.
- ✓ Textile harness. Plastic headgear.
- ✓ Ratchet headgear.
- ✓ With comfortable foam pad in the back.
- ✓ Front comfortable sweatband.
- ✓ Colors and versions: see below.
- ✓ Weight: 380 grams.
- → Packing: carton of 20 units.
 - bundle of 5 units.
 - individual polybag.



Learn more on www.singer.fr

>> Main advantages

- ✓ Very convenient use provided with the ratchet system adjustment. (53 cm to 66 cm).
- ✓ Very comfortable and good stability (8 points harness!), light weight and resistant.
- ✓ Foam pad in the back for increased comfort.
- ✓ Many accessories available (ear-muffs, visors...).

>> Conformity

This product has been tested according to the following European Standards:

- EN 397: 2012 +A1: 2012. Industrial safety helmet
- EN 50365: 2002. Electrically Insulating Helmets for use on low voltage installations. Class 0. 1000 Vac.

It complies with European Regulation (EU) 2016/425 on Personal Protective Equipment (PPE). Category III.

EU type examination certificate (module B) issued by **BSI**. Notified body **n°0086**.

The PPE is subject to the conformity assessment procedure based on quality assurance of the production process (**Module D**) set out in Annex VIII (Category III) under surveillance of **BSI**. Notified body **n°0086**.

Download the EU declaration of conformity on: http://docs.singer.fr

Ref	FORCE2W	FORCE2B	FORCE2O
Very low temperature	-30 ° C	-30 ° C	-30 ° C
Electric insulation	440 Vac	440 Vac	440 Vac
Molten metal splash	MM	MM	MM
Electrical insulation Low voltage	会	会	A
Headgear sizing range	53-66cm	53-66cm	53-66cm
Version	Non-ventilated	Non-ventilated	Non-ventilated

C € 0086

Your SINGER® SAFETY's partner

