



>> **Type of use (\*)**

This garment is for signaling the user's presence visually, intended to provide conspicuity of the user in hazardous situations under any light conditions by day and under illumination by vehicle headlights in the dark. Road maintenance, maintenance of parks and gardens, public works professions, transport, construction, dockers, movers, tour guides, security jobs...

>> **Technical features**

- ✓ **Description:** high-visibility bodywarmer. With retro-reflective tapes. Outer pockets. Rest pockets. 1 inner pocket. Front zipper fastening. Features a zip access for print.
- ✓ **Outshell:** polyester **Oxford 300D** with polyurethane coating.
- ✓ **Lining:** 100% polyester polar fleece lining, **260 gsm**.
- ✓ **Colour:** yellow. Grey tapes.
- ✓ **Sizes and packaging**

	M, L, XL, 2XL	S, 3XL	
Carton	10 units	5 units	
Bundle	1 unit	1 unit	

Learn more : [www.singer.fr](http://www.singer.fr)

>> **Main advantages**

- ✓ Good quality of workmanship and materials.
- ✓ Retro-reflective tapes above the shoulders for good visibility even above the wearer (good visibility for example from crane operators on construction sites!).
- ✓ Straight collar for neck protection against cold and rain..
- ✓ Warm and comfortable.

>> **Compliance**

This garment has been tested according to the following European Standards (**Category II**).

- **EN ISO 13688: 2013.** Protective garment. General requirements.
- **EN ISO 20471: 2013.** High visibility clothing - Test methods and requirements

It complies with the European Regulation (**EU 2016/425** on Personal Protective Equipment (**PPE**)).  
EU examination type certificate (**module B**) issued by **CENTEXBEL**, notified body n°0493.

EN ISO 20471: 2013 +A1 : 2016




**Also available in**  
**orange colour**  
**Ref: GANO**



Your distributor **SINGER® SAFETY**

**SINGER®**   
safety

SIZES	CHEST (cm) (A)	HEIGHT (cm) (B)
S	84-96	160-172
M	92-104	166-178
L	100-112	172-184
XL	108-120	180-192
2XL	116-128	188-198
3XL	126-138	192-202



<b>EN ISO 20471: 2013 +A1 : 2016</b>	
	Result ▼
Background & Retro-reflective material	Class 2

**Information about classes**  
 Class 3: highest level of visibility. Class 2: intermediate visibility level.  
 Class 1: lowest level of visibility.

Minimum area requirement in m <sup>2</sup>	Class 3 garment	Class 2 garment	Class 1 garment
Background material	0.80	0.50	0.14
Retro-reflective material	0.20	0.13	0.10
Combined performance material			0.20

**Background fluorescent coloured material, for the day**  
 Fluorescence is the ability of a material to reflect more light than it receives.  
 Consequently fluorescent colors seem more vivid than those which does not have this property.

**Retro-reflective material for night**  
 A retro-reflector is a device capable of reflecting the light it receives back in directions close to the source. Thus the driver who light a pedestrian in the night with the headlights of his vehicle, can identifies very quickly the garment which features a retro-reflective material.

The coefficient of retro-reflection of the retro-reflective material must be class 2 to comply with EN ISO 20471 (class 1 of previous EN 471 standard has been cancelled).

(x) the figure next to the pictogram indicates the category of the garment according to the minimum area requirement in m<sup>2</sup>.

Your distributor **SINGER® SAFETY**

