



>> Use (\*)

Thanks to a careful workmanship and a strict selection of materials, this equipment can be used for indoor or outdoor work activities, for many jobs in the industry, logistics, transport, parks maintenance, crafts or building and public works...

>> Technical features

- ✓ Winter safety boots.
- ✓ Water repellent pigmented leather upper.
- ✓ 200J shockproof steel toe cap.
- ✓ Acrylic fur lining.
- ✓ Perforated, antistatic and removable insole made of EVA fabric.
- ✓ Steel puncture resistant midsole.
- ✓ Double-density polyurethane sole.
- ✓ Black colour. Grey stitching.
- ✓ Size : 39 to 47.
- ✓ Packing : Carton of 10 pairs.  
Bundle of 1 pair.



Learn more : [www.singer.fr](http://www.singer.fr)

Advantages

- ✓ A boot with a modern and dynamic look.
- ✓ Soft, durable and waterproof leather.
- ✓ PU reinforcements at the ends of the boot enhance durability and performance of the product.
- ✓ Acrylic fur lining for comfort and optimum insulation in winter.
- ✓ Dual density polyurethane outsole designed to provide better slip resistance and abrasion.
- ✓ Energy absorbing heel.
- ✓ Practical grip handles for easy donning.

>> Conformity

This product has been tested according to the following European Standard:

- EN ISO 20345: 2011 Personal protective equipment — Safety footwear

It complies with the European Regulation (EU) 2016/425 on Personal Protective Equipment (PPE).

(Category II)

EU type examination certificate (module B) issued by INTERTEK Italia Spa. Notified body n° 2575.



Protection	Symbol <b>S3</b>	Basic properties plus (Toe protection against shocks equivalent to a level of energy equal to 200J and the risks of flattening under a maximal weight of 15Kn.) + closed backpart + antistatic properties + energy absorption of the heel + resistance to fuel oil + water penetration and water absorption + anti-puncture sole + studded sole.
Slip resistance	Symbol <b>SRC</b>	(= SRA + SRB) Slip resistance on ceramic tile floor with SLS and on steel floor with glycerol

Your distributor **SINGER® SAFETY**

