

**SNR**  
**27,6dB**

**WEIGHT**  
**168g**



### >> Type of use (\*)

This equipment provides excellent protection by filtering out high-frequency noises that can be met near rotating machines such as workshop machinery, motorized saws etc. Industry, machine shops, automotive assembly, airports, printing works, carpentry, construction, sheet-metal shops, lawn mowing etc..

### >> Technical features

- ✓ Ear muff made of two red cups tied together with a headband.
- ✓ The yellow cups are pressed against each outer ear through the black plastic headband.
- ✓ This device is adjustable by the motion of the cups on the headband.
- ✓ Each cup features a comfortable black cushion and are filled with foam.
- ✓ Headband equipped with a comfort foam pad.
- ✓ **Weight:** 168 grams.
- ✓ **Packing:** - carton of 60 pieces.  
- box of of 10 pieces.  
- each piece under individual polybag.



Learn more: [www.singer.fr](http://www.singer.fr)

### >> Advantages

- ✓ Practical and lightweight.
- ✓ Good level of attenuation.
- ✓ Good value for money.
- ✓ Adjustable; fits easily on most heads
- ✓ Comfortable foam pad on headband.

### >> Conformity

This product has been tested according to the following European standard:

- **EN 352-1: 2002.** Hearing protection. Part 1. Ear-muffs.

It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category III.**

EU type examination certificate (**module B**) issued by **BSI (Netherlands)**. Notified body **n°2797**.

The PPE is subject to the conformity assessment procedure based on quality assurance of the production process (**Module D**) set out in Annex VIII (Category III) under surveillance of **BSI**. notified body **n°2797**.

Download the EU declaration of conformity on: <http://docs.singer.fr>

Values of sound attenuation

SNR value in accordance with ISO / DIS 4869-2 with parameter  $\alpha = 1$

SNR value : **27,6 dB (H = 30,4 dB M = 24,9 dB L = 17,7 dB)**

Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
Mean attenuation (dB)	19.0	16.0	18.3	25.9	30.6	31.7	34.5	38.1
Standard deviation	5.7	5.0	2.5	2.8	1.6	3.4	2.8	2.6
APV (dB)	13.3	11.0	15.8	23.1	28.9	28.3	31.7	35.5



Your distributor **SINGER® SAFETY**

