



SNR	WEIGHT
26,3dB	174g

Lightweight



>>Use (*)

When worn properly and given adequate care, it provides excellent protection that filters high frequency noise which we find most noise problems from dynamic machine such as workshop equipment, motor saws.

Loud noise in the workplace can be very damaging to hearing and it usually happens gradually so that employees are not aware of the dangers until they have developed permanent hearing loss. As well as gradual hearing loss, there is also hearing loss that results from sudden and extremely loud noises.

These earmuffs help reduce exposure to hazardous noise and other loud sounds

Industry, maintenance of parks and gardens, public works professions, forestry development, airports.

>> Technical features

- ✓ Lightweight and foldable ear-defender.
- ✓ Adjustable grey cups.
- ✓ Gloss finish.
- ✓ Headband equipped with a comfort foam pad.
- ✓ High comfortable black cushions.
- ✓ High density inner foam.
- ✓ Handy pocket size.
- ✓ Weight: 174 grams.
- ✓ Packing: - carton of 24 blisters.
- individual blister.



Learn more: www.singer.fr

>> Advantages

- ✓ Ultra compact and lightweight !
- ✓ Superior quality of cushions, insulating foam.
- ✓ Comfort fit and wearing even during prolonged use (comfort foam).
- ✓ Fully adjustable model.

>> Conformity

This product has been tested according to the following European standard:

EN 352-1: 2002. Hearing protection. Part 1. Ear-muffs.

It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category III.**

EU type examination certificate (**module B**) issued by **ALIENOR**. Notified body **n°2754**.

The PPE is subject to the conformity assessment procedure based on quality assurance of the production process (**Module D**) set out in Annex VIII (Category III) under surveillance of **INSPEC**. Notified body **n°0194**.

Download the EU type declaration of conformity on: <http://docs.singer.fr>

Values of sound attenuation / SNR value in accordance with ISO / DIS 4869-2 with parameter $\alpha = 1$

SNR value: **26,3 dB (H:31,8 dB M:23,6 dB L: 14,9 dB)**

Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
Mean attenuation (dB)	15.7	11.4	15.5	25.7	34.4	34.1	35.9	35.3
Standard deviation	3.4	3.1	2.7	2.6	2.7	4.2	2.6	2.7
APV (dB)	12.3	8.3	12.8	23.1	31.7	29.9	33.3	32.5



Your distributor **SINGER® SAFETY**

