LAURO

Shoes - Construction



⁽¹⁾Approximative weight of a shoe (smaller size)

>> Advantages

- 3 flex zones on the sole for an optimal flexibility
- Energy absorbing heel.



>> Use (*)

Thanks to a careful workmanship and a strict selection of materials, this equipment can be used for indoor or outdoor work activities, for many jobs in the industry, logistics, transport, parks maintenance, crafts or building and public works...



>> Technical features

- High cut safety shoes.
- Water repellent full grain leather. Metal hooks fastening.
- ✓ Composite 200J toe cap.
- Gusset tongue.
- → Perforated, antistatic and removable insole made of EVA fabric.
- High strength textile puncture resistant midsole.
- Double-density polyurethane injected sole.
- Black Colour. Grey and red stitching.
- ✓ Sizes : 39 to 47.
- Packing : Carton of 10 pairs.
 Bundle of 1 pair.



CE

Learn more : www.singer.fr



>> Compliance

This safety shoe has been tested according to the following European Standard (Category II).

- EN ISO 20345: 2012. Personal protective equipment - Safety footwear.

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (**PPE**). EU type examination certificate (**module B**) issued by **INTERTEK Italia Spa.** Notified body **n°2575**. Download the EU declaration of conformity on: http://docs.singer.fr

Protection	Symbol S3	Basic properties plus (Toe protection against shocks equivalent to a level of energy equal to 200J and the risks of flattening under a maximal weight of 15Kn.) + closed backpart + antistatic properties + energy absorption of the heel + resistance to fuel oil + water penetration and water absorption + anti-puncture sole + studded sole.
Slip resistance	Symbol SRC	(= SRA + SRB) Slip resistance on ceramic tile floor with SLS and on steel floor with glycerol

Your partner SINGER® SAFETY

