



>> Type of use (*)

Soft, resistant and comfortable, mechanics gloves can be used in many activities at work or for leisure and sport activities.

Plumbing. Joinery work. Bricklayer. Plumbers. Carpenters, Bricklayers. Do-it-yourself. Leisure. Mechanic sport. Cycling.

>> Technical features

- ✓ Cut-and-sewn safety glove
- ✓ Mechanic style.
- ✓ Sizes 8, 9, 10.
- ✓ Palm in 65% nylon + 35% PU.
- ✓ Back in 97% polyester + 3% Elastane.
- ✓ Self-grip closure for best wrist fitting.
- ✓ Reinforced palm.
- ✓ Cut-fingers (forefinger and thumb) style.

✓ Packing:

- Bundle of 10 pairs.
- Each pair under individual polybag.



Learn more: www.singer.fr



>> Advantages

- ✓ ISO 9001 system in production.
- ✓ Quality of materials and excellent workmanship.
- ✓ Ideally shaped to the contours of the hand for comfort and dexterity.
- ✓ Various reinforcements on the palm ensure a longer service life.

>> Conformity

This glove has been tested according to the following European standards :


- EN 420 : 2003 + A1 : 2009. Protective gloves - General requirements and test methods.
- EN 388 : 2016. Protective gloves against mechanicals risks.

It complies with European Regulation (EU) 2016/425 on Personal Protective Equipment (PPE). Category II. EU type examination certificate (module B) issued by CENTEXBEL. Notified body n°0493.

Download the EU declaration of conformity on: <http://docs.singer.fr>



EN 388: 2016. Protective gloves against mechanical risks

Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels ▼	EN 388 : 2016  1 1 1 1 X
Abrasion resistance (number of cycles)	100	500	2000	8000	-	1	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	1	
Tear resistance (in Newtons)	10	25	50	75	-	1	
Perforation resistance (in Newtons)	20	60	100	150	-	1	
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level
	2	5	10	15	22	30	X

«X» means that the glove has not been submitted to the test.

Your distributor SINGER® SAFETY

