


15 GAUGE

>>Type of use (\*)

Thanks to its technical characteristics, this glove is particularly suitable for all the main light jobs requiring dexterity as well as works in wet conditions. General handling, driver, warehousing, storage, maintenance of green areas, packaging, logging... For masons, roofers, landscapers, carpenters, gardeners ...

>> Technical features

- ✓ **Construction:** knitted seamless pattern, with water repellent treatment. Elastic knitted wrist. Open back version. 15 gauge.
  - ✓ **Materials:**
    - Liner in polyamide.
    - Coating: special P.V.C foam coating. Knuckled coated version. HPT™ (encapsulated air molecules). (HPT Hydropellent Technology™). With Actifresh®.
  - ✓ **Colour:** black liner & coating.
  - ✓ **Sizes:** 7, 8, 9, 10.
  - ✓ **Packing:** - carton of 100 pairs. - bundle of 10 pairs.
- Learn more: [www.singer.fr](http://www.singer.fr)



>> Advantages

- ✓ **Seamless construction:** improves user comfort (will avoid rough points and consequently the risks of reddening or irritation of the skin). Improves dexterity for easy handling of small parts and reduces hand fatigue.
- ✓ **The CFT (Compressed Formula Technology) HPT™ (Hydropellent technology)** coating process creates a thin layer of material that is flexible, consistent and durable. This unique material repels liquids and offers to the user an exceptional good grip even in wet conditions! Encapsulated air molecules provide an inherent vibration absorption feature.
- ✓ **Elasticated knitted wrist** for a snug fit.
- ✓ **Actifresh®** treatment protection against the development of the mould, especially in a humid environment, a protection against microbial attacks, a protection against a discolouration, prevents the bacteria action from bad smell.
- ✓ The guarantee and benefits of an **ISO 9001** certified manufacturing: quality of products, regularity...

>> Conformity

This glove has been tested as per:

- **EN 420 : 2003 +A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanical risks.

It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.** EU type-examination certification issued by **SATRA (Ireland)**. Notified body n°2777.

Download the EU declaration of conformity on: <http://docs.singer.fr>



EN 388 : 2016. Protective gloves against mechanical risks							
Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels ▼	
Abrasion resistance (number of cycles)	100	500	2000	8000	-	<b>3</b>	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	<b>1</b>	
Tear resistance (in Newtons)	10	25	50	75	-	<b>3</b>	
Perforation resistance (in Newtons)	20	60	100	150	-	<b>1</b>	
Cut resistance (N) (as per EN ISO13997) (TDM test) «X» means that the glove has not been submitted to the test.	Level A	Level B	Level C	Level D	Level E	Level F	Level
	2	5	10	15	22	30	<b>X</b>

**EN 388 : 2016**

3 1 3 1 X

Your **SINGER® SAFETY** partner



(\*) Type of use is given as a guide only. It is to the end user to check whether the product is suitable or not for the intended use. Before any use, read carefully the instructions enclosed with the product. Issue U.S.\_2019\_05\_22. Copyright: Singer, Fotolia