




>> Type of use (\*)

Thanks to its technical features, this glove is particularly suitable for all heavy works requiring good strength as well as good resistances in oily and / or fatty environments: automobile assembly, automobile repair, construction, public works, metal works, raw material handling, sharp handling sheets, household refuse collection, handling abrasive materials, deep sea fishing, maintenance of public parks...

>> Technical features

- ✓ **Construction / material:** Cut and sewn liner. Nitrile knuckle coated. Heavy coating. 100% cotton fleece liner. Open back (ventilated). Knitted wrist.
- ✓ **Color:** natural liner / blue coating.
- ✓ **Sizes:** 8, 9, 10.
- ✓ **Packing:** - carton of 100 pairs. - bundle of 10 pairs. 



Learn more: [www.singer.fr](http://www.singer.fr)



>> Advantages

- ✓ Heavy coating on a fleece lining for a maximum protection and comfort.
- ✓ The open back improves the hand ventilation.

>> Conformity

This glove has been tested according to the following European standards :


- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanicals risks.



It complies with **European Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**

EU type examination certificate (module B) issued by the **CTC**. Notified body **n°0075**.

**EN 388: 2016. Protective gloves against mechanical risks**

Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels ▼	<b>EN 388 : 2016</b>  <b>4 1 1 1 X</b>
Abrasion resistance (number of cycles)	100	500	2000	8000	-	<b>4</b>	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	<b>1</b>	
Tear resistance (in Newtons)	10	25	50	75	-	<b>1</b>	
Perforation resistance (in Newtons)	20	60	100	150	-	<b>1</b>	
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level
	2	5	10	15	22	30	<b>X</b>

«X» means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**

