Nitrile coating - Cut-and-sewn liner

N B R 3 2 6



>> Type of use (*)

Thanks to its technical features, this glove is particularly suitable for all heavy works requiring good strength as well as good resistances in oily and / or fatty environments: automobile assembly, automobile repair, construction, public works, metal works, raw material handling, sharp handling sheets, household refuse collection, handling abrasive materials, deep sea fishing, maintenance of public parks...

>> General features

- Construction, materials: cut and sewn pattern.
 100% brushed cotton liner. Heavy nitrile knuckle coating.
 Open back. Knitted wrist. With Sanitized[®].
- Colour: natural colour liner / blue coating.
- ✓ Sizes: 8, 9, 10.
- Packing: Cartons of 100 pairs.
 Bundles of 10 pairs.

CE

More information: www.singer.fr



>> Advantages

- ✓ The guarantee and benefits of an ISO 9001 certified manufacturing: quality of products, regularity ...
- Brushed cotton liner: brings the comfort of a natural material which facilitates the absorption of perspiration
- The heavy coating provides an excellent resistance for demanding works and for jobs needing extra protection.
- Open back style allows excellent breathability.
- Anti-bacterial effect of the Actifresh[®] treatment deprives bacteria from developing and growing. The **Sanitized[®]** treatment is effective against bacteria, fungi, rust, stains and algae in preventing these micro-organisms from developing. It promotes a longer life and avoids the creation of bad odours.
- Knitted wrist securely holds the glove in place during use.

>> Conformity

This glove has been tested as per:

- EN 420 : 2003 +A1 : 2009. Protective gloves General requirements and test methods.
- EN 388 : 2016. Protective gloves against mechanical risks.

It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (**PPE**). **Category II.** EU type-examination certification issued by **SATRA (Ireland).** Notified body **n°2777**.

Download the EU declaration of conformity on: http://docs.singer.fr

Mechanical data. nformation about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels V 4 1 2		EN 388 : 201
Abrasion resistance (number of cycles)	100	500	2000	8000	-			
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0			▏▎▎▎▎▎
Fear resistance (in Newtons)	10	25	50	75	-			
Perforation resistance (in Newtons)	20	60	100	150	-	1		
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level	4121B
	2	5	10	15	22	30	В	

Your distributor SINGER® SAFETY

SINGER® safety