



Stretch nylon + cotton

>> Type of use

Thanks to its technical characteristics, this glove is particularly suitable for all light handling in dry conditions.

Automotive assembly, warehouse & package, shipping & receiving, electronics industry, assembly stations, handling boxes, quality controls...

>> Technical features

- ✓ **Construction:** seamless knitted pattern. Elastic knitted wrist. Dotted palm.
- ✓ **Liner:** plaited, stretch nylon outer, cotton inner.
- ✓ **Gauge:** 13.
- ✓ **Coating:** P.V.C dots on palm.
- ✓ **Colour:** white liner / blue dots.
- ✓ **Sizes:** 6, 7, 8, 9.
- ✓ **Packing:** - carton of 100 pairs.
- bundle of 10 pairs.



Learn more: www.singer.fr



>> Advantages

- ✓ Outstanding fit, flexibility and feel.
- ✓ The soft seamless liner provides exceptional comfort, reduces hand fatigue and will not irritate hand-even during long periods of wear.
- ✓ Elasticated knitted wrist for a snug fit.
- ✓ The back of the glove uncoated allowing the hand to breathe.
- ✓ P.V.C dotted palm: excellent grip in dry conditions for safe and secure handling of small parts and tools or fine handling tasks.
- ✓ Polyamide fibres: the polyamide fibre offers high toughness. It is resistant against mold and fungus. It is low water absorbent.
- ✓ Plaited cotton: the inner surface of the glove (plaited cotton) brings the comfort of a natural fiber.
- ✓ **ISO 9001** certification for a regular and good quality of products.

>> Conformity

This glove has been tested as per:

- **EN 420 : 2003 +A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanical risks.


It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**

EU type-examination certification issued by **SATRA (Ireland)**. Notified body **n°2777**.

Download the EU declaration of conformity on: <http://docs.singer.fr>



EN 388: 2016. Protective gloves against mechanical risks

Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels ▼	EN 388 : 2016  2 1 4 1 X
Abrasion resistance (number of cycles)	100	500	2000	8000	-	2	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	1	
Tear resistance (in Newtons)	10	25	50	75	-	4	
Perforation resistance (in Newtons)	20	60	100	150	-	1	
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level
	2	5	10	15	22	30	X

(*) «X» means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**

