

Knuckle coated



>> Use (\*)

Thanks to its technical characteristics, this glove is suitable for all light and medium works in wet and/or fat/oily conditions, requiring good dexterity and protection against mechanical risks in particular abrasion: automotive assembly, precision engineering, industrial maintenance, repair of mechanical parts, electronic industry, small parts assembly...

>> Technical features

- ✓ **Construction:** seamless machine knit glove.
- ✓ **Elasticated knitted wrist.** Polyester fibres.
- ✓ **Gauge :** 13.
- ✓ **Coating :** nitrile coating on palm and back (fully coated).
- ✓ **Color :** black coating, black liner.
- ✓ **Sizes :** 7, 8, 9, 10, 11.
- ✓ **Packing :** - carton of 100 pairs.  
- bundle of 10 pairs.



Learn more : [www.singer.fr](http://www.singer.fr)



>> Main advantages

- ✓ The gloves are machine knitted liners made from Polyester / Elastane which gives good fit and sensitivity, superior comfort and dexterity.
- ✓ The seamless liner provides exceptional comfort and reduces hand fatigue.
- ✓ The polyester fibre offers high toughness, it provides good resistance against abrasion; it is resistant against mold and fungus. It is low water absorbent.
- ✓ Elasticated knitted wrist for a snug fit.
- ✓ Nitrile provides good protection against oil and grease.

>> Conformity

This glove has been tested according to the following European standards :

- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanicals risks.



It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.** EU type examination certificate (module B) issued by the **CTC**. Notified body n°0075.

Download the EU declaration of conformity on: <http://docs.singer.fr>

EN 388: 2016. Protective gloves against mechanical risks							
Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels ▼	<b>EN 388 : 2016</b>  <b>3 1 2 1 X</b>
Abrasion resistance (number of cycles)	100	500	2000	8000	-	<b>3</b>	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	<b>1</b>	
Tear resistance (in Newtons)	10	25	50	75	-	<b>2</b>	
Perforation resistance (in Newtons)	20	60	100	150	-	<b>1</b>	
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level
	2	5	10	15	22	30	<b>X</b>

«X» means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**



(\*) Type of use is given as a guide only. It is to the end user to check whether the product is suitable or not for the intended use. Before any use, read carefully the instructions enclosed with the product. Issue U.S. 2019.03.28. Copyright: Singer, F. Colliat