


Knuckle coated



>> Type of use (*)

Thanks to its technical characteristics, this glove is particularly suitable for all the main light works requiring good dexterity and protection against mechanical risks, particularly abrasion, in wet and oily environments: automotive assembly, precision engineering, industrial maintenance, repair of mechanical parts, electronic industry, small parts assembly ...

>> Technical data

- ✓ **Construction:** knitted seamless pattern.
- ✓ Knitted wrist. Liner in polyester fibres.
- ✓ **Gauge:** 15.
- ✓ **Coating:** flat nitrile coating on palm and back (fully coated version). With **Sanitized®**.
- ✓ **Colour:** black coating, black liner.
- ✓ **Sizes:** 6, 7, 8, 9, 10, 11.
- ✓ **Packing:** - carton of 100 pairs.  - bundle of 10 pairs.

Learn more: www.singer.fr



>> Main advantages

- ✓ **Seamless construction:** improves user comfort (will avoid rough points and consequently the risks of reddening or irritation of the skin). Improves dexterity for easy handling of small parts and reduces hand fatigue.
- ✓ **Polyester fibres:** the polyester fibre offers high toughness, it provides good resistance against abrasion; it is resistant against mold and fungus. It is low water absorbent.
- ✓ **Elasticated knitted wrist** for a better comfort and a perfect fit of the glove on the hand
- ✓ **Protective coating:** the nitrile flat coating will bring you additional protection specially against oils and fats. Fully coated version for a whole and excellent protection of the hand.
- ✓ **ISO9001** certification for a regular and good quality of products
- ✓ **Sanitized®** treatment protection against the development of the mould, especially in a humid environment, a protection against microbial attacks, a protection against a discolouration, prevents the bacteria action from bad smell.

>> Conformity


This glove has been tested according to the following European standards :

- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanicals risks.



It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.** EU type examination certificate (module B) issued by **SATRA (Irland)**. Notified body n°2777.

Download the EU declaration of conformity on: <http://docs.singer.fr>

EN 388: 2016. Protective gloves against mechanical risks								EN 388 : 2016
Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels ▼	 4 1 2 1 X	
Abrasion resistance (number of cycles)	100	500	2000	8000	-	4		
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	1		
Tear resistance (in Newtons)	10	25	50	75	-	2		
Perforation resistance (in Newtons)	20	60	100	150	-	1		
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level	
	2	5	10	15	22	30	X	

«X» means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**



(*) Type of use is given as a guide only. It is to the end user to check whether the product is suitable or not for the intended use. Before any use, read carefully the instructions enclosed with the product. Issue U.S. 2019.02.06. Copyright: Singer, F. Italia