



>>Type of use (*)

Thanks to its technical characteristics, this glove is particularly suitable for all major works requiring good dexterity in dry environments.

General handling with tools, handling raw materials, machine operator, outdoor works (gardening, lawn care, landscaping), assembly and construction, bricklayers, roofers, plumbers ...



>> Technical features

- ✓ **Construction:** seamless knitted type glove. Elasticated knitted wrist. Open back (uncoated).
- ✓ **Liner:** polyester fibres.
- ✓ **Gauge:** 15.
- ✓ **Coating:** natural latex on palm and fingers.
- ✓ **Colour:** bright yellow liner; black coating.
- ✓ **Sizes:** 8, 9, 10.
- ✓ **Packing:** - cartons of 100 pairs.
- bundles of 10 pairs.



Learn more: www.singer.fr



>> Advantages

- ✓ **Seamless pattern:** enhances user comfort (no roughness, points of overheating) and reduces hand fatigue. Improves dexterity for handling small parts.
- ✓ **Knitted wrist:** for a better elasticity and a perfect fit of the glove on the hand.
- ✓ **Protective coating:** the latex coating on palm provides additional protection to the user as well as an excellent grip to handle small objects.
- ✓ Treated with **Actifresh®** to kill bacteria and promote freshness.
- ✓ **Comfort open back:** allows a good ventilation of the hand and for better hygiene.

>> Conformity

This glove has been tested according to the following European standards :

- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanicals risks.



It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.** EU type examination certificate (module B) issued by **SATRA (Ireland)**. Notified body n°2777.

Download the EU declaration of conformity on: <http://docs.singer.fr>

EN 388: 2016. Protective gloves against mechanical risks							
Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels ▼	
Abrasion resistance (number of cycles)	100	500	2000	8000	-	2	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	1	
Tear resistance (in Newtons)	10	25	50	75	-	3	
Perforation resistance (in Newtons)	20	60	100	150	-	1	
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level
	2	5	10	15	22	30	X

EN 388 : 2016

2 1 3 1 X

«X» means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**



(*) Type of use is given as a guide only. It is to the end user to check whether the product is suitable or not for the intended use. Before any use, read carefully the instructions enclosed with the product. Issue US_2019.01.09. Copyright: Singer, Foblia.