

Hard-wearing material reinforcement



>> Use (\*)

Thanks to its technical characteristics, this glove is suitable for all major works requiring dexterity and a significant protection against mechanical risks including cut (TDM level D). Industrial maintenance, automotive assembly, general handling, making cables, cardboard factory, metal sheet manufacture, aircraft assembly, ...

>> Technical features

- ✓ **Construction:** Seamless knitted liner, long elasticated knitted wrist. HDPE fibers (High Density Polyethylene).
- ✓ **Coating :** Soft polyurethane coating on palm (Open back).
- ✓ **Colour :** grey.
- ✓ **Gauge :** 13.
- ✓ **Sizes :** 7, 8, 9, 10, 11.
- ✓ **Packing :** Carton of 100 pairs. Bundle of 10 pairs.



Learn more : [www.singer.fr](http://www.singer.fr)

>> Main advantages

- ✓ **Seamless knitted liner :** It provides comfort (no roughness or warm-up spots). It increases dexterity for fine object handling.
- ✓ **High-density fibers :** HDPE fibers provides excellent protection against mechanical risks (including the cut).
- ✓ **Protective coating:** The PU coating on palm provides an additional protection to the user and better grip of the handled objects.
- ✓ **Long protection wrist:** For a better protection of the forearm.
- ✓ **Crotch reinforcement between thumb and forefinger :** it reinforces the fragile point of the gloves.

>> Conformity

This glove has been tested according to the following European standards:

- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanicals risks.



It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**

EU type examination certificate (module B) issued by the **CTC**. Notified body **n°0075**.

Download the EC declaration of conformity on: <http://docs.singer.fr>

EN 388: 2016. Mechanical data (information about levels)	Level 1	Level 2	Level 3	Level 4	Level 5	Levels ▼	EN 388 : 2016
Abrasion resistance (number of cycles)	100	500	2000	8000	-	4	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	X	
Tear resistance (in Newtons)	10	25	50	75	-	4	
Puncture resistance (in Newtons)	20	60	100	150	-	3	
Cut resistance (N) as per EN ISO 13997	Level A	Level B	Level C	Level D	Level E	Level F	Level ▼
	2	5	10	15	22	30	D

◁X means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**



(\*) Type of use is given as a guide only. It is to the end user to check whether the product is suitable or not for the intended use. Before any use, read carefully the instructions enclosed with the product. Issue CL 29-04-2019. Copyright: Singer