




Cut protection

>> Use (\*)

Thanks to its technical characteristics, this glove is suitable for all major works requiring dexterity and a significant protection against mechanical risks including cut. Industrial maintenance, automotive assembly, general handling, making cables, handling sharp objects, raw materials...

>> Technical features

- ✓ **Construction:** seamless knitted pattern.  
Liner made up of high density polyethylene fibres (HDPE)  
Elasticated knitted wrist. Open back.
- ✓ **Colour:** grey liner / grey coating.
- ✓ **Gauge:** 13.
- ✓ **Coating:** soft polyurethane (PU) coating on palm (open back).
- ✓ **Sizes:** 6, 7, 8, 9, 10, 11.
- ✓ **Packing:** Carton of 100 pairs.  
Bundle of 10 pairs. 

More information: [www.singer.fr](http://www.singer.fr)

>> Advantages

- ✓ These gloves provide a good cut resistance, while providing greater dexterity and comfort.
- ✓ This product provides good protection against abrasion and tear in dry conditions handling.
- ✓ Elasticated knitted wrist for a snug fit.
- ✓ The seamless liner provides exceptional comfort and reduces hand fatigue.
- ✓ The back of the glove uncoated allowing the hand to breathe.
- ✓ Excellent grip in dry conditions for safe and secure handling.
- ✓ The **ISO 9001 / ISO 14001** certified production guarantees the reliability / regularity of the production and the control of the environmental impact.

>> Conformity


This glove has been tested according to the following European standards :

- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanicals risks.

It complies with **European Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**  
EU type examination certificate (module B) issued by the **CTC**, notified body **n°0075**.



**EN 388: 2016. Protective gloves against mechanical risks**

Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels ▼	<b>EN 388 : 2016</b>  <b>4 X 4 3 D</b>
Abrasion resistance (number of cycles)	100	500	2000	8000	-	<b>4</b>	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	<b>X</b>	
Tear resistance (in Newtons)	10	25	50	75	-	<b>4</b>	
Perforation resistance (in Newtons)	20	60	100	150	-	<b>3</b>	
Cut resistance (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level
	2	5	10	15	22	30	<b>D</b>

«X» means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**



(\*) Type of use is given as a guide only. It is to the end user to check whether the product is suitable or not for the intended use. Before any use, read carefully the instructions enclosed with the product. Issue CL 14/05/2018. Copyright: Singer. Fotolia.