Construction & Public works, finishings



>>Use ^(*)


This model can be used in construction & public works, finishings...

Bricklayers, crane operators, carpenters, plumbers, tilers, roofers, house painters, dry wall installers, construction equipment operators, work drivers, etc.

>> Technical features

- High cut safety shoes.
- ✓ Top of upper with lining.
- Full piece removable footbed.
- ✓ Tongue gusset.
- Textile pierce resistant midsole.
 Energy absorbing heel.
- Fastening with laces and D rings.
- Black colour with orange contrasts.
- ✓ Sizes: 39 to 47.
- Packaging: Carton of 10 pairs.

Learn more: www.singer.fr





CE

⁽¹⁾Approximative weight of a shoe (smaller size)

670g⁽¹⁾

>> Advantages

- Convenient full piece and removable footbed. Dual-density PU outsole.
- Energy absorption of heel. Comfortable and lightweight shoe.
- Upper with soft and strong leather. Quality of materials and workmanship.
- ✓ Soft and lightweight textile pierce resistant midsole. With composite toe cap.
- ✓ Good ankle support. Reinforcements at each end for longer service life.



>> Compliance

This safety shoe has been tested according to the following European Standard (Category II).

- EN ISO 20345: 2012. Personal protective equipment - Safety footwear.

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (**PPE**). EU type examination certificate (**module B**) issued by **CIMAC (Italy)**, notified body **n°0465**.

Protection	Symbol S3	Basic properties plus (Toe protection against shocks equivalent to a level of energy equal to 200J and the risks of flattening under a maximal weight of 15Kn.) + closed backpart + antistatic properties + energy absorption of the heel + resistance to fuel oil + wate r penetration and water absorption + anti-puncture sole + studded sole.
Slip resistance	Symbol SRC	(= SRA + SRB) Slip resistance on ceramic tile floor with SLS and on steel floor with glycerol

Your distributor SINGER® SAFETY

