

Reinforced at each end



640g<sup>(1)</sup>

<sup>(1)</sup> Approximative weight of a shoe (smaller size)

>> Use (\*)

Thanks to its technical characteristics this product is ideal for your work in industrial environment and more generally for protection against projections thanks to its closure system with leather flap.

>> Technical features

- ✓ Safety boot.
- ✓ Leather upper.
- ✓ Top of upper with lining.
- ✓ Full piece removable footbed.
- ✓ Pierce resistant midsole and safety toe cap.
- ✓ Energy absorbing heel.
- ✓ Polyurethane (PU) double density sole.
- ✓ Easy closing system with leather cover and self-grip system.
- ✓ Protection against splashes.
- ✓ Reinforced at each end.
- ✓ Colour: black.
- ✓ Sizes: 39 to 47.
- ✓ Packaging: - Carton of 10 pairs.  
- Each pair individually packed in a box.



Learn more: [www.singer.fr](http://www.singer.fr)

>> Advantages

- ✓ Convenient full piece and removable footbed.
- ✓ Dual-density PU outsole.
- ✓ Energy absorption of heel.
- ✓ Upper in soft and strong leather.
- ✓ Quality of materials and workmanship.
- ✓ Fast and easy closing system



>> Conformity

This product has been tested according to the following European Standard:

- **EN ISO 20345: 2011** Personal protective equipment — Safety footwear

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE).

(Category II)

EU type examination certificate (module B) issued by **INTERTEK Italia Spa**. Notified body n°2575.

Download the EU declaration of conformity on: <http://docs.singer.fr>



Protection	Symbol <b>S1-P</b>	General requirement of the standard EN ISO 20345. Steel toe-protector absorbs an energy of 200 J + closed back, anti-static properties, heel energy absorption. Shoes with pierce resistant midsole up to 1100 newtons.
Slip resistance	Symbol <b>SRC</b>	(= SRA +SRB) Slip resistance on ceramic tile floor with SLS and on steel floor with glycerol.

Your distributor **SINGER® SAFETY**

