

>>Type of use (*)



>> Technical features

- → Double lanyard (rope) in polyamide.
- → 3 strand polyamide rope.
- ✓ Length: 1,50 m.
- → Diameter: 12 mm.
- → With energy absorber, karabiner and hook at each end.
 - → Packing:
 - carton of 10 piece.
 - bundle of 1 piece.



Learn more: www.singer.fr

>> Advantages

- ▼ The spliced end is protected with a strong transparent protective covering sleeve.
- This not only protects the splicing but also make the splicing visible for easy inspection prior to use.
- → The loops at the end are protected by an abrasion resistant thimble. This prevents the rope from being damaged
 by the metallic contact of the connector.
- The rope also has a coloured tracer strand which loses its colour in due course of time, to show that the lanyard is now unfit for further use.
- For application where 100% tie-off is required, mostly in situations where the user has to change position frequently while working, climbing up or down.
- → The energy absorbing forked lanyards offer the facility of attaching one lanyard and detaching the other lanyard thereby making the user secure at all times.

>> Conformity

This product has been tested according to the following European standard:

- EN 355: 2002. Personal protective equipment against falls from a height. Energy absorbers.
- CNB/P/11.063: 2014. Co-ordination of notified bodies. Vertical Recommendation for Use sheets (RfUs). VG11.

It complies with European Regulation (EU) 2016/425 on Personal Protective Equipment (PPE). Category III.

EU type examination certificate (module B) issued by SATRA (Ireland). Notified body n°2777.

The PPE is subject to the conformity assessment procedure based on quality assurance of the production process (**Module D**) set out in Annex VIII (Category III) under surveillance of **SGS Fimko Oy (Finland)**. Notified body **n°0598**.

Download the EU declaration of conformity on: http://docs.singer.fr

Your distributor SINGER® SAFETY



